

**1 Identification of the substance or mixture and of the supplier****Product identifier**Trade name: **SPRAY P340 PLASTOFIX**

Article number: 632

Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture Surface protection

**Details of the supplier of the safety data sheet**

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Emergency telephone number: 24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

**2 Hazards identification****Classification of the substance or mixture**

flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



Skin Irrit. 2 H315 Causes skin irritation.

Additional information:

6.3A Substances that are irritating to the skin

**Trade name: SPRAY P340 PLASTOFIX**

2.1.2A Flammable aerosol

2.1.1 AFlammable gas - high hazard

**Label elements**

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Other hazards**

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

**3 Composition/Information on ingredients****Chemical characterisation: Mixtures**

· Description: Mixture of hazardous substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 1330-20-7	xylene	50-<60%
EINECS: 215-535-7	Flam. Liq. 3, H226	
Index number: 601-022-00-9	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
RTECS: ZE 2100000		
CAS: 106-97-8	butane, pure	30-<35%
EINECS: 203-448-7	Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
RTECS: EJ 4200000	Acute Tox. 3, H331	
CAS: 67-64-1	acetone	1-<5%
EINECS: 200-662-2	Flam. Liq. 2, H225	
Index number: 606-001-00-8	Eye Irrit. 2, H319; STOT SE 3, H336	
RTECS: AL 3150000		
CAS: 75-28-5	isobutane	1-<5%
EINECS: 200-857-2	Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
RTECS: TZ 4300000		
CAS: 74-98-6	propane	1-<5%
EINECS: 200-827-9	Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas C, H280	
RTECS: TX 2275000		

Continue on page 3

NZ

**Trade name: SPRAY P340 PLASTOFIX**

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures****Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire fighting measures****Extinguishing media**

- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**  
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- **Speial protective equipment and fire fighting procedures:** No special measures required.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures**

- Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage****Handling:**

- Precautions for safe handling No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- Requirements to be met by storerooms and receptacles:  
Observe official regulations on storing packagings with pressurised containers.

## Trade name: **SPRAY P340 PLASTOFIX**

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

### **8 Exposure controls/personal protection**

#### **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

##### **1330-20-7 xylene**

WES (New Zealand) Long-term value: 217 mg/m<sup>3</sup>, 50 ppm  
oto

IOELV (EU) Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin

##### **106-97-8 butane, pure**

WES (New Zealand) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

##### **67-64-1 acetone**

WES (New Zealand) Short-term value: 2375 mg/m<sup>3</sup>, 1000 ppm  
Long-term value: 1185 mg/m<sup>3</sup>, 500 ppm  
bio

IOELV (EU) Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

##### **74-98-6 propane**

WES (New Zealand) Simple asphyxiant; may present an explosion hazard

- Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

- Additional information: The lists valid during the making were used as basis.

#### **Exposure controls**

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 5  
NZ

**Trade name: SPRAY P340 PLASTOFIX**

- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:  
Rubber gloves
- Eye protection: Not required.
- Body protection: Protective work clothing

**9 Physical and chemical properties****Information on basic physical and chemical properties**

## · General Information

## · Appearance:

## · Form:

Aerosol

## · Colour:

According to product specification

## · Odour:

Characteristic

## · Odour threshold:

Not determined.

## · pH-value:

Mixture is non-soluble (in water).

## · Change in condition

## · Melting point/freezing point:

Undetermined.

## · Initial boiling point and boiling range:

-44.5 °C

## · Flash point:

&lt; 0 °C

## · Flammability (solid, gas):

Not applicable.

## · Autoignition temperature:

365 °C

## · Decomposition temperature:

Not determined.

## · Ignition temperature:

Product is not selfigniting.

## · Explosive properties:

Risk of explosion by shock, friction, fire or other sources of ignition.

## · Explosion limits:

## · Lower:

1.1 Vol %

## · Upper:

8.5 Vol %

## · Vapour pressure at 20 °C:

2,100 hPa

## · Density at 20 °C:

0.869 g/cm<sup>3</sup>

## · Relative density

Not determined.

## · Vapour density

Not determined.

## · Evaporation rate

Not applicable.

## · Solubility in / Miscibility with

## · water:

Fully miscible.

## · Partition coefficient: n-octanol/water:

Not determined.

## · Viscosity:

## · Dynamic:

Not determined.

## · Kinematic:

Not determined.

## · Solvent content:

## · Organic solvents:

93.3 %

## · VOC (EC)

845.5 g/l

## · Solids content (volume):

2.5 %

· **Other information**

No further relevant information available.

## Trade name: **SPRAY P340 PLASTOFIX**

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- Acute toxicity
- LD/LC50 values relevant for classification:

---

**ATE (Acute Toxicity Estimates)**
  - Dermal LD50 3.795 mg/kg (rabbit)
  - Inhalative LC50/4 h 20.7 mg/l**1330-20-7 xylene**
  - Oral LD50 4,300 mg/kg (rat)
  - Dermal LD50 2,000 mg/kg (rabbit)
  - Inhalative LC50/4 h 11 mg/l (ATE)**106-97-8 butane, pure**
  - Inhalative LC50/4 h 658 mg/l (rat)**67-64-1 acetone**
  - Oral LD50 5,800 mg/kg (rat)
  - Dermal LD50 20,000 mg/kg (rabbit)
- Primary irritant effect:
  - Skin corrosion/irritation Irritant to skin and mucous membranes.
  - Serious eye damage/irritation No irritating effect.
  - Respiratory or skin sensitisation Sensitising effect through inhalation is possible by prolonged exposure.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

### 12 Ecological information

- **Toxicity**
- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **Behaviour in environmental systems:**
  - Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.

**Trade name: SPRAY P340 PLASTOFIX**

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

\* **14 Transport information**

· **UN-Number**

- NZS, IMDG, IATA UN1950

· **UN proper shipping name**

- NZS UN1950 AEROSOLS
- IMDG AEROSOLS
- IATA AEROSOLS, flammable

· **Transport hazard class(es)**

- NZS



- Class 2.5F Gases.
- Label 2.1
- IMDG, IATA



- Class 2.1 Gases.
- Label 2.1

· **Packing group**

- NZS, IMDG, IATA Void

· **Environmental hazards:**

- Marine pollutant: No

· **Special precautions for user**

- Warning: Gases.

- Hazard identification number (Kemler code): -

**Trade name: SPRAY P340 PLASTOFIX**

· EMS Number:	F-D,S-U
· Segregation groups	(SGG10) Liquid halogenated hydrocarbons
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· NZS	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

\* **15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· **New Zealand Inventory of Chemicals**

All ingredients are listed.

· **HSNO Approval numbers**

HSNO Number/HSNO Group Standard HSR002515

1330-20-7 xylene: HSR000983

106-97-8 butane, pure: HSR000989

67-64-1 acetone: HSR001070

75-28-5 isobutane: HSR001003

74-98-6 propane: HSR001010

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07



**Trade name: SPRAY P340 PLASTOFIX**

- Signal word Danger
- Hazard statements  
H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.  
H315 Causes skin irritation.
- Precautionary statements  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

**16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Reasons for alterations
- Relevant phrases  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.
- **Department issuing SDS:** Department of Quality Control
- **Contact:**  
HB BODY S.A  
Ms Olympia Stamkou  
Ph: +30 2310 790 032  
fax: +30 2310 790 033  
email: stamkou@hbbody.com
- \* Data compared to the previous version altered.

## Trade name: **SPRAY P340 PLASTOFIX**

### \* **Annex: Exposure scenario 1**

#### · **Short title of the exposure scenario**

##### · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

##### · Product category PC9b Fillers, putties, plasters, modelling clay

##### · Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

##### · Article category AC1 Vehicles

##### · Environmental release category ERC2 Formulation into mixture

#### · **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

##### · **Conditions of use** According to directions for use.

##### · **Duration and frequency** Frequency of use:

##### · **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

##### · **Physical state** Aerosol

##### · **Concentration of the substance in the mixture** The substance is main component.

##### · **Used amount per time or activity** Smaller than 100 g per application.

##### · **Other operational conditions**

##### · **Other operational conditions affecting environmental exposure** No special measures required.

##### · **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

##### · **Other operational conditions affecting consumer exposure**

No special measures required.

Keep out of the reach of children.

##### · **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

##### · **Risk management measures**

##### · **Worker protection**

##### · **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

##### · **Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

##### · **Personal protective measures**

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Use suitable respiratory protective device in case of insufficient ventilation.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Tightly sealed goggles

Continue on page 11

NZ

**Trade name: SPRAY P340 PLASTOFIX****· Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Keep locked up and out of the reach of children.

**· Environmental protection measures****· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

**· Soil** The product is only processed over the concrete collecting basin.**· Disposal measures** Ensure that waste is collected and contained.**· Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

**· Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

## Trade name: **SPRAY P340 PLASTOFIX**

### \* **Annex: Exposure scenario 2**

#### · **Short title of the exposure scenario**

- Sector of Use SU9 Manufacture of fine chemicals
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- Technical function Solvent

#### · **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

- **Conditions of use** According to directions for use.

- Duration and frequency Frequency of use:

#### · **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- Physical state Fluid
- Concentration of the substance in the mixture Raw material.
- Used amount per time or activity Smaller than 5000 kg per application.

#### · **Other operational conditions**

- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure  
Avoid contact with the skin.  
Do not breathe gas/vapour/aerosol.  
Take precautionary measures against static discharge.  
Keep away from sources of ignition - No smoking.
- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

#### · **Risk management measures**

- Worker protection
- Organisational protective measures  
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- Technical protective measures  
Ensure that suitable extractors are available on processing machines  
Provide explosion-proof electrical equipment.
- Personal protective measures  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Measures for consumer protection  
Ensure adequate labelling.  
Observe consumer information and advice on safe use.

**Trade name: SPRAY P340 PLASTOFIX**· **Environmental protection measures**· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.· **Disposal measures** Ensure that waste is collected and contained.· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging· **Exposure estimation**· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ  
Continue on page 14

**Trade name: SPRAY P340 PLASTOFIX**

**Annex: Exposure scenario 3**

**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.

**Duration and frequency** Frequency of use:

**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Fluid

**Concentration of the substance in the mixture** Raw material.

**Other operational conditions**

**Other operational conditions affecting environmental exposure** No special measures required.

**Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

**Other operational conditions affecting consumer exposure** No special measures required.

**Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

**Risk management measures**

**Worker protection**

**Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**Environmental protection measures**

**Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

**Soil** The product is only processed over the concrete collecting basin.

**Disposal measures** Ensure that waste is collected and contained.

**Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Waste type** Partially emptied and uncleaned packaging

**Exposure estimation**

**Consumer**

This product is to be used by professional technicians only.

**Trade name: SPRAY P340 PLASTOFIX**

Not relevant for this Exposure Scenario.

**Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ