

1 Identification**1.1 Product identifier**Trade name: **BUMPER PAINT TEXTURE**

Article number: 356

Application of the substance / the mixture

Coating compound/ Surface coating/ paint

Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

H.B. BODY S.A

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

email: hbody@hbody.com

Information department:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbody.com

email: hbody@hbody.com

1.4 Emergency telephone number: CHEMTRECK : 800-494-9300**2 Hazard(s) identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

Carbon black
ethylbenzene

· Hazard statements

H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H351 Suspected of causing cancer. Route of exposure: Inhalation.

· Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



HEALTH 1 Health = 1
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

· **2.3 Other hazards**

· Results of PBT and vPvB assessment

· PBT: Not applicable.
· vPvB: Not applicable.

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 2)

3 Composition/information on ingredients

3.2 Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7	xylene	30-<35%
EINECS: 215-535-7	Flammable Liquids 3, H226	
Index number: 601-022-00-9	Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315	
RTECS: ZE 2100000		
CAS: 123-86-4	n-butyl acetate	15-<20%
EINECS: 204-658-1	Flammable Liquids 3, H226	
Index number: 607-025-00-1	Specific Target Organ Toxicity - Single Exposure 3, H336	
RTECS: AF 7350000		
CAS: 471-34-1	calcium carbonate	10-<15%
EINECS: 207-439-9		
RTECS: EV 9580000		
CAS: 84540-57-8	methoxypropyl acetate	5-<10%
EINECS: 283-152-2	Flammable Liquids 3, H226	
CAS: 1333-86-4	Carbon black	1-<5%
EINECS: 215-609-9	Carcinogenicity 2, H351	
RTECS: FF 5150100		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1-<5%
EINECS: 203-603-9	Flammable Liquids 3, H226	
Index number: 607-195-00-7		
CAS: 100-41-4	ethylbenzene	≥0.1-<0.9%
EINECS: 202-849-4	Flammable Liquids 2, H225	
Index number: 601-023-00-4	Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304	
RTECS: DA 0700000	Acute Toxicity - Inhalation 4, H332	

4 First-aid measures

4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

- Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- Protective equipment: No special measures required.

(Contd. on page 4)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 3)

- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

-
- 1330-20-7 xylene: 130 ppm
 - 123-86-4 n-butyl acetate: 5 ppm
 - 471-34-1 calcium carbonate: 45 mg/m³
 - 1333-86-4 Carbon black: 9 mg/m³
 - 108-65-6 2-methoxy-1-methylethyl acetate: 50 ppm
 - Polyethylene: 16 mg/m³
 - 100-41-4 ethylbenzene: 33 ppm
 - 108-90-7 chlorobenzene: 10 ppm
 - 112945-52-5 Silica dioxide: 18 mg/m³
 - 1330-20-7 xylene: 130 ppm
 - 78-83-1 butanol: 150 ppm

PAC-2:

-
- 1330-20-7 xylene: 920* ppm
 - 123-86-4 n-butyl acetate: 200 ppm
 - 471-34-1 calcium carbonate: 210 mg/m³
 - 1333-86-4 Carbon black: 99 mg/m³
 - 108-65-6 2-methoxy-1-methylethyl acetate: 1,000 ppm
 - Polyethylene: 170 mg/m³
 - 100-41-4 ethylbenzene: 1100* ppm
 - 108-90-7 chlorobenzene: 150 ppm
 - 112945-52-5 Silica dioxide: 100 mg/m³
 - 1330-20-7 xylene: 920* ppm
 - 78-83-1 butanol: 1,300 ppm

PAC-3:

-
- 1330-20-7 xylene: 2500* ppm
 - 123-86-4 n-butyl acetate: 3000* ppm
 - 471-34-1 calcium carbonate: 1,300 mg/m³
 - 1333-86-4 Carbon black: 590 mg/m³
 - 108-65-6 2-methoxy-1-methylethyl acetate: 5000* ppm

(Contd. on page 5)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 4)

- Polyethylene: 1,000 mg/m³
- 100-41-4 ethylbenzene: 1800* ppm
- 108-90-7 chlorobenzene: 400 ppm
- 112945-52-5 Silica dioxide: 630 mg/m³
- 1330-20-7 xylene: 2500* ppm
- 78-83-1 butanol: 8000* ppm

7 Handling and storage

- 7.1 Precautions for safe handling** Open and handle receptacle with care.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep receptacle tightly sealed.
- 7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- 8.1 Control parameters**
- Components with limit values that require monitoring at the workplace:
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.
- 1330-20-7 xylene**
PEL Long-term value: 435 mg/m³, 100 ppm
REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV Long-term value: 20 ppm
BEI, A4
- 123-86-4 n-butyl acetate**
PEL Long-term value: 710 mg/m³, 150 ppm
REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm
TLV Short-term value: 150 ppm
Long-term value: 50 ppm
- 471-34-1 calcium carbonate**
PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction
REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction
TLV TLV withdrawn
- 1333-86-4 Carbon black**
PEL Long-term value: 3.5 mg/m³

(Contd. on page 6)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 5)

REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³
*inhalable fraction, A3

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
OTO, BEI, A3

· **Regulatory information**

PEL: Guide to Occupational Exposure Values (OSHA PELs)
REL: Guide to Occupational Exposure Values (NIOSH RELs)
TLV: Guide to Occupational Exposure Values (TLV)
WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 6)

- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

- Form: Fluid
- Color: According to product specification
- Odor: Characteristic
- Odor threshold: Not determined.
- pH-value: Mixture is non-soluble (in water).

· Change in condition

- Melting point/Melting range: Undetermined.
- Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F)
- Flash point: 23 - 60 °C (73.4 - 140 °F)
- Flammability (solid, gaseous): Flammable.
- Auto igniting: 333 °C (631.4 °F)
- Decomposition temperature: Not determined.
- Ignition temperature: Product is not selfigniting.
- Danger of explosion: Risk of explosion by shock, friction, fire or other sources of ignition.
- Explosion limits:
 - Lower: 1.1 Vol %
 - Upper: 7.5 Vol %
- Vapor pressure at 20 °C (68 °F): 10.7 hPa (8 mm Hg)
- Density at 20 °C (68 °F): 1.053 g/cm³ (8.78729 lbs/gal)
- Relative density: Not determined.
- Vapor density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with
 - Water: Fully miscible.
- Partition coefficient (n-octanol/water): Not determined.
- Viscosity:
 - Dynamic: Not determined.
 - Kinematic: Not determined.

(Contd. on page 8)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 7)

- Solvent content:
 - Organic solvents: 51.4 %
 - VOC content: 51.41-51.44 %
541.7 g/l / 4.52 lb/gal
 - Solids content: 40.8 %
- **9.2 Other information** No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on toxicological effects**
 - Acute toxicity: Based on available data, the classification criteria are not met.
 - LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 6,526 mg/kg
Inhalative LC50/4 h 35.9 mg/l

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

471-34-1 calcium carbonate

Oral LD50 6,450 mg/kg (rat)

84540-57-8 methoxypropyl acetate

Oral LD50 8,532 mg/kg (rat)
Dermal LD50 5,000 mg/kg (rab)

1333-86-4 Carbon black

Oral LD50 10,000 mg/kg (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)
Inhalative LC50/4 h 35.7 mg/l (rat)

100-41-4 ethylbenzene

Oral LD50 3,500 mg/kg (rat)
Dermal LD50 17,800 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

(Contd. on page 9)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 8)

- Primary irritant effect:
 - on the skin:
Causes skin irritation.
 - on the eye: Based on available data, the classification criteria are not met.
- Sensitization: Based on available data, the classification criteria are not met.
- Additional toxicological information:
 - Carcinogenic categories
 - IARC (International Agency for Research on Cancer)

 - 1330-20-7 xylene: 3
 - 9003-55-8 resin: 3
 - 1333-86-4 Carbon black: 2B
 - Polyethylene: 3
 - 100-41-4 ethylbenzene: 2B
 - 1330-20-7 xylene: 3
 - NTP (National Toxicology Program)

 - None of the ingredients is listed.
 - OSHA-Ca (Occupational Safety & Health Administration)

 - None of the ingredients is listed.
 - Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - Carcinogenicity
Suspected of causing cancer. Route of exposure: Inhalation.
 - Reproductive toxicity Based on available data, the classification criteria are not met.
 - Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.
 - Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.
 - Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
 - General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 9)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

14.1 UN-Number

· DOT, ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

· DOT Paint
· ADR UN1263 PAINT
· IMDG, IATA PAINT

14.3 Transport hazard class(es)

· DOT



· Class 3 Flammable liquids
· Label 3
· ADR



· Class 3 (F1) Flammable liquids
· Label 3
· IMDG, IATA



· Class 3 Flammable liquids
· Label 3

14.4 Packing group

· DOT, ADR, IMDG, IATA III

14.5 Environmental hazards:

· Marine pollutant: No

14.6 Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler code): 30

· EMS Number: F-E, S-E

· Segregation groups (SGG10) Liquid halogenated hydrocarbons

· Stowage Category A

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 11)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

15 Regulatory information

·3Y

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

108-90-7 chlorobenzene

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

1330-20-7 xylene: ACTIVE

9003-55-8 resin: ACTIVE

123-86-4 n-butyl acetate: ACTIVE

471-34-1 calcium carbonate: ACTIVE

1333-86-4 Carbon black: ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate: ACTIVE

68609-36-9 modified chlorinated polyolefin: ACTIVE

1302-78-9 bentonite: ACTIVE

Polyethylene: ACTIVE

100-41-4 ethylbenzene: ACTIVE

108-90-7 chlorobenzene: ACTIVE

61789-01-3 epoxidised oil: ACTIVE

68937-54-2 Siloxanes and silicones, di-Me, 3-hydroxypropyl-Me, ethoxylated: ACTIVE

1330-20-7 xylene: ACTIVE

78-83-1 butanol: ACTIVE

· Hazardous Air Pollutants

1330-20-7 xylene

100-41-4 ethylbenzene

108-90-7 chlorobenzene

1330-20-7 xylene

(Contd. on page 12)

US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 11)

- Proposition 65
- Chemicals known to cause cancer:

1333-86-4 Carbon black
100-41-4 ethylbenzene
- Chemicals known to cause reproductive toxicity for females:


None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.
- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.
- Cancerogenicity categories
- EPA (Environmental Protection Agency)

1330-20-7 xylene: I
100-41-4 ethylbenzene: D
108-90-7 chlorobenzene: D
1330-20-7 xylene: I
- TLV (Threshold Limit Value)

1330-20-7 xylene: A4
1333-86-4 Carbon black: A4
100-41-4 ethylbenzene: A3
108-90-7 chlorobenzene: A3
1330-20-7 xylene: A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labeled according to the CLP regulation.
- Hazard pictograms

GHS02 GHS07 GHS08
- Signal word Warning
- Hazard-determining components of labeling:
Carbon black
ethylbenzene
- Hazard statements
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
- Precautionary statements
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash thoroughly after handling.

(Contd. on page 13)
US

Trade name: BUMPER PAINT TEXTURE

(Contd. of page 12)

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P370+P378	In case of fire: Use CO2, powder or water spray to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Department of Quality Control

· **Contact:**

H.B BODY S.A
Ms Olympia Stamkou
Ph: +30 2310 790 032
fax: +30 2310 790 033

· **Date of preparation / last revision** 03/17/2023

· * Data compared to the previous version altered.