

1 Identification of the substance or mixture and of the supplier**Product identifier**Trade name: **C494 CLEAR ULTRA HS 2:1**

Article number: 365

Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category

PC9b Fillers, putties, plasters, modelling clay

PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture

Coating compound/ Surface coating/ paint

Surface protection

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Emergency telephone number: 24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

2 Hazards identification**Classification of the substance or mixture**

Flam. Liq. 3

H226 Flammable liquid and vapour.

Trade name: C494 CLEAR ULTRA HS 2:1



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **Additional information:**

3.1B Flammable liquid

3.1C Flammable liquid

9.1C Substances that are harmful in the aquatic environment

6.9 (Narcotic) Substances that are harmful to human target organs or systems

· **Label elements**

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/Information on ingredients

· **Chemical characterisation: Mixtures**

· Description: Mixture of hazardous substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 8050-15-5	Methyl ester of rosin (partially hydrogenated)	50-<60%
EINECS: 232-476-2	Aquatic Chronic 3, H412	

Continue on page 3

NZ

Trade name: C494 CLEAR ULTRA HS 2:1

CAS: 123-86-4	n-butyl acetate	20-<25%
EINECS: 204-658-1	Flam. Liq. 3, H226	
Index number: 607-025-00-1	STOT SE 3, H336	
RTECS: AF 7350000		
CAS: 112-07-2	2-butoxyethyl acetate	5-<10%
EINECS: 203-933-3	Acute Tox. 4, H312; Acute Tox. 4, H332	
Index number: 607-038-00-2	Flam. Liq. 4, H227	
RTECS: KJ 8925000		
CAS: 1330-20-7	xylene	5-<10%
Index number: 601-022-00-9	Flam. Liq. 3, H226	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1-<5%
EINECS: 203-603-9	Flam. Liq. 3, H226	
Index number: 607-195-00-7		
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≥0.25-<0.9%
EINECS: 255-437-1	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Skin Sens. 1, H317	
CAS: 82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	≥0.1-<0.25%
EINECS: 280-060-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Skin Sens. 1, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures**Description of first aid measures****· General information:**

Take affected persons out into the fresh air.

Seek immediate medical advice.

Immediately remove any clothing soiled by the product.

· After inhalation: Seek medical treatment in case of complaints.**· After skin contact:** Immediately rinse with water.**· After eye contact:** Rinse opened eye for several minutes under running water.**· After swallowing:** If symptoms persist consult doctor.**· Information for doctor:**

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures**Extinguishing media****· Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

· Speial protective equipment and fire fighting procedures: Wear self-contained respiratory protective device.**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Continue on page 4

NZ

Trade name: C494 CLEAR ULTRA HS 2:1

HAZ CHEM CODE: 3YE

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage**Handling:****Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities**Storage:**

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

Specific end use(s) No further relevant information available.**8 Exposure controls/personal protection****Control parameters****Ingredients with limit values that require monitoring at the workplace:****123-86-4 n-butyl acetate**WES (New Zealand) Short-term value: 950 mg/m³, 200 ppmLong-term value: 713 mg/m³, 150 ppm

IOELV (EU)

Short-term value: 723 mg/m³, 150 ppmLong-term value: 241 mg/m³, 50 ppm**112-07-2 2-butoxyethyl acetate**

IOELV (EU)

Short-term value: 333 mg/m³, 50 ppmLong-term value: 133 mg/m³, 20 ppm

Skin

Continue on page 5

NZ

Trade name: C494 CLEAR ULTRA HS 2:1**1330-20-7 xylene**

WES (New Zealand) Long-term value: 217 mg/m³, 50 ppm
oto

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin

108-65-6 2-methoxy-1-methylethyl acetate

IOELV (EU) Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin

· **Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· Additional information: The lists valid during the making were used as basis.

· **Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Trade name: C494 CLEAR ULTRA HS 2:1**9 Physical and chemical properties****Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Mixture is non-soluble (in water).

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	124-128 °C
Flash point:	23 - 60 °C
Flammability (solid, gas):	Flammable.
Autoignition temperature:	280 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	0.89443 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	45.8 %
VOC (EC)	409.8 g/l
Solids content (volume):	2.2 %

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Continue on page 7

NZ

Trade name: **C494 CLEAR ULTRA HS 2:1**

- **Hazardous decomposition products:** No dangerous decomposition products known.

* 11 Toxicological information

· **Information on toxicological effects**

- Acute toxicity
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 10,848 mg/kg (rabbit)
Inhalative LC50/4 h 68.4 mg/l

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral LD50 2,400 mg/kg (rat)
Dermal LD50 1,580 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)
Inhalative LC50/4 h 35.7 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation No irritant effect.
- Serious eye damage/irritation No irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.

* 12 Ecological information

· **Toxicity**

· Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **Behaviour in environmental systems:**

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

· **Ecotoxic effects:**

- Remark: Harmful to fish

· **Additional ecological information:**

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Trade name: C494 CLEAR ULTRA HS 2:1

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

Results of PBT and vPvB assessment

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **Other adverse effects** No further relevant information available.

13 Disposal considerations**Waste treatment methods**

- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information**UN-Number**

- NZS, IMDG, IATA UN1263

UN proper shipping name

- NZS UN1263 PAINT
- IMDG, IATA PAINT

Transport hazard class(es)

- NZS



- Class 3 (F1) Flammable liquids.
- Label 3
- IMDG, IATA



- Class 3 Flammable liquids.
- Label 3

Packing group

- NZS, IMDG, IATA III

Environmental hazards:

- Marine pollutant: No

Special precautions for user

- Warning: Flammable liquids.
- Hazard identification number (Kemler code): 30
- EMS Number: F-E, S-E
- Stowage Category A

Trade name: C494 CLEAR ULTRA HS 2:1

- **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- NZS
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E
- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- IATA
- Remarks: HAZ CHEM CODE: 3YE
- **UN "Model Regulation":** UN 1263 PAINT, 3, III

15 Regulatory information

•3Y

Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

New Zealand Inventory of Chemicals

All ingredients are listed.

HSNO Approval numbers

HSNO Approval number HSR 002662
Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006
HSNO Hazard classification Refer to section 2

123-86-4 n-butyl acetate: HSR001091

112-07-2 2-butoxyethyl acetate: HSR001155

1330-20-7 xylene: HSR000983

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Trade name: C494 CLEAR ULTRA HS 2:1

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Reasons for alterations
- Relevant phrases
 - H226 Flammable liquid and vapour.
 - H227 Combustible liquid.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H332 Harmful if inhaled.
 - H336 May cause drowsiness or dizziness.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Department of Quality Control
- **Contact:**
 - HB BODY S.A
 - Ms Olympia Stamkou
 - Ph: +30 2310 790 032
 - fax: +30 2310 790 033
 - email: stamkou@hbbody.com
- * Data compared to the previous version altered.

Trade name: C494 CLEAR ULTRA HS 2:1**Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category

PC9b Fillers, putties, plasters, modelling clay

PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Article category AC1 Vehicles**Environmental release category ERC2 Formulation into mixture****Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** Use only on hard ground.**Other operational conditions affecting worker exposure**

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Do not breathe gas/vapour/aerosol.

Other operational conditions affecting consumer exposure No special measures required.**Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Use product only in enclosed systems.

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Continue on page 12

NZ

Trade name: C494 CLEAR ULTRA HS 2:1

- **Measures for consumer protection**
Ensure adequate labelling.
Observe consumer information and advice on safe use.
- **Environmental protection measures**
- **Water**
Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
Do not allow to reach sewage system.
- **Soil**
Prevent contamination of soil.
The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer**
This product is to be used by professional technicians only.
Not relevant for this Exposure Scenario.
- **Guidance for downstream users**
Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.