

SECTION 1: Identifikacija hemikalije i podaci o licu koje stavlja hemikaliju u promet**1.1 Product identifier**Trade name: **600 PAINT REMOVER SPRAY**

Article number: 494

UFI: U770-S07R-N007-D2Q3

1.2 Relevant identified uses of the substance or mixture and uses advised against**Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

SECTION 2: Identifikacija opasnosti**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Trade name: **600 PAINT REMOVER SPRAY**

- Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
 The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:
 dimethoxymethane
- Hazard statements
 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
- Precautionary statements
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
 Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Sastav/Podaci o sastojcima

3.2 Mixtures

- Description: Mixture of hazardous substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 646-06-0	1,3-dioxolane	40-<45%
EINECS: 211-463-5	Flam. Liq. 2, H225	
Index number: 605-017-00-2		
RTECS: JH 6760000		
CAS: 115-10-6	dimethyl ether	35-<40%
EINECS: 204-065-8	Flam. Gas 1A, H220	
Index number: 603-019-00-8	Acute Tox. 2, H330	
RTECS: PM 4780000	Press. Gas (Comp.), H280	
CAS: 109-87-5	dimethoxymethane	15-<20%
EINECS: 203-714-2	Flam. Liq. 2, H225	
RTECS: PA 8750000	Skin Sens. 1, H317	

Continue on page 3
 RS

Trade name: **600 PAINT REMOVER SPRAY**

CAS: 108-01-0	2-dimethylaminoethanol	1-<5%
EINECS: 203-542-8	Flam. Liq. 3, H226	
Index number: 603-047-00-0	Skin Corr. 1B, H314	
RTECS: KK 6125000	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
	Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	

CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	1-<5%
EINECS: 265-149-8	Flam. Liq. 3, H226	
Index number: 649-422-00-2	Asp. Tox. 1, H304	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: Mere prve pomoæi

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Mere za gašenje požara

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards

Special protective equipment and fire fighting procedures: No special measures required.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Mere u sluèaju udesa

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

Trade name: 600 PAINT REMOVER SPRAY

See Section 13 for disposal information.

SECTION 7: Rukovanje i skladištenje

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 Do not spray onto a naked flame or any incandescent material.
 Keep ignition sources away - Do not smoke.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- Requirements to be met by storerooms and receptacles:
 Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Kontrola izloženosti

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

- IOELV (EU) Long-term value: 1920 mg/m³, 1000 ppm
- Regulatory information IOELV (EU): (EU) 2019/1831
- Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- Respiratory protection:
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Use suitable respiratory protective device in case of insufficient ventilation.
- Hand protection



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 5
 RS

Trade name: 600 PAINT REMOVER SPRAY

- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye/face protection
Safety glasses



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Fizička i hemijska svojstva

9.1 Information on basic physical and chemical properties

General Information

- | | |
|--|------------------------------------|
| · Physical state | Aerosol |
| · Colour: | Colourless |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | -24.9 °C (115-10-6 dimethyl ether) |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 2.1 Vol % |
| · Upper: | 20.5 Vol % |
| · Flash point: | < 0 °C |
| · Autoignition temperature: | 235 °C |
| · Decomposition temperature: | Not determined. |
| · pH | Mixture is non-soluble (in water). |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Fully miscible. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 5,200 hPa |
| · Density and/or relative density | |
| · Density at 20 °C: | 0.857 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

9.2 Other information

- Appearance:
- Form: Gaseous
- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

Continue on page 6

RS

Trade name: 600 PAINT REMOVER SPRAY

· Solvent content:	
· Organic solvents:	35.8 %
· VOC (EC)	306.4 g/l
· Solids content (volume):	16.8 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Reaktivnost i stabilnost

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toksikološki podaci**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	102,622 mg/kg (rat)
Dermal	LD50	70,296 mg/kg (rabbit)
Inhalative	LC50/4 h	167 mg/l

Continue on page 7
RS

Trade name: 600 PAINT REMOVER SPRAY**646-06-0 1,3-dioxolane**

Oral LD50 3,000 mg/kg (rat)

Dermal LD50 8,480 mg/kg (rabbit)

Inhalative LC50/4 h 20,650 mg/l (rat)

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

109-87-5 dimethoxymethane

Oral LD50 5,708 mg/kg (rabbit)

108-01-0 2-dimethylaminoethanol

Oral LD50 2,000 mg/kg (rat)

Dermal LD50 1,370 mg/kg (rabbit)

Inhalative LC50/4 h 3.25 mg/l (mouse)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards**Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ekotoksikološki podaci**12.1 Toxicity****Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment**

· PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Continue on page 8

RS

Trade name: 600 PAINT REMOVER SPRAY

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Odlaganje**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

HP3 Flammable

HP13 Sensitising

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Podaci o transportu**14.1 UN number or ID number**

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

UN1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class

2.5F Gases.

Label

2.1

IMDG, IATA



Class

2.1 Gases.

Label

2.1

14.4 Packing group

ADR, IMDG, IATA

Void

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Gases.

Hazard identification number (Kemler code):

-

EMS Number:

F-D,S-U

Continue on page 9

RS

Trade name: 600 PAINT REMOVER SPRAY

· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatorni podaci

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:
dimethoxymethane
- Hazard statements
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Continue on page 10
RS

Trade name: 600 PAINT REMOVER SPRAY

- P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.**SECTION 16: Ostali podaci**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

· Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1 Bridging principles

Skin corrosion/irritation The classification of the mixture is generally based on the calculation method using

Serious eye damage/irritation substance data according to Regulation (EC) No 1272/2008.

Skin sensitisation

· Contact:

HB BODY S.A

Ms Olympia Stamkou

Trade name: 600 PAINT REMOVER SPRAY

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

· Date of previous version: 26.10.2021

· Version number of previous version: 8

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· * Data compared to the previous version altered.

Trade name: 600 PAINT REMOVER SPRAY**Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers**Process category**

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Article category AC1 Vehicles**Environmental release category ERC2** Formulation into mixture**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Aerosol**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** No special measures required.**Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

Other operational conditions affecting consumer exposure Keep out of the reach of children.**Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Tightly sealed goggles

Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Trade name: 600 PAINT REMOVER SPRAY

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· Soil The product is only processed over the concrete collecting basin.**· Disposal measures** Ensure that waste is collected and contained.**· Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.