

**SECTION 1: Identifikacija hemikalije i podaci o licu koje stavlja hemikaliju u promet****1.1 Product identifier**Trade name: **BODY 640 CAVITY WAX**

Article number: 470

UFI: E4P1-G07C-U001-CMFU

**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC7 Industrial spraying

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

Article category AC2 Machinery, mechanical appliances, electrical/electronic articles

Application of the substance / the mixture Surface protection

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

**Further information obtainable from:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

**SECTION 2: Identifikacija opasnosti****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Continue on page 2

RS

## Trade name: **BODY 640 CAVITY WAX**



GHS07

- Skin Irrit. 2      H315 Causes skin irritation.
- STOT SE 3      H336 May cause drowsiness or dizziness.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

### · **2.2 Label elements**

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### · Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labelling:  
 Low boiling point hydrogen treated naphtha  
 toluene  
 Naphtha (petroleum), hydrotreated light
- Hazard statements  
 H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H361d Suspected of damaging the unborn child.  
 H336 May cause drowsiness or dizziness.  
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

## \* **SECTION 3: Sastav/Podaci o sastojcima**

### · **3.2 Mixtures**

- Description: Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 3  
 RS

## Trade name: **BODY 640 CAVITY WAX**

### Dangerous components:

CAS: 64742-82-1	Low boiling point hydrogen treated naphtha	30-<35%
EINECS: 265-185-4	Flam. Liq. 3, H226	
Index number: 649-330-00-2	STOT RE 1, H372; Asp. Tox. 1, H304	
Reg.nr.: 01-2119458049-33-0002	STOT SE 3, H336	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	20-<25%
EINECS: 265-151-9	Flam. Liq. 2, H225	
Index number: 649-328-00-1	Asp. Tox. 1, H304	
Reg.nr.: 01-2119475514-35-0001	Aquatic Chronic 2, H411	
	Skin Irrit. 2, H315; STOT SE 3, H336	
	EUH066	
CAS: 108-88-3	toluene	≥3-<5%
EINECS: 203-625-9	Flam. Liq. 2, H225	
Index number: 601-021-00-3	Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304	
RTECS: XS 5250000	Skin Irrit. 2, H315; STOT SE 3, H336	
Reg.nr.: 01-2119471310-51-0000		
01-2119471310-51-0003		
01-2119471310-51-0005		
01-2119471310-51-0002		
01-2119471310-51-0027		
CAS: 68037-49-0	Sulfonic acids, C10-18-alkane, sodium salts	1-<5%
EINECS: 268-213-3	Acute Tox. 4, H302	
CAS: 64742-82-1	Low boiling point hydrogen treated naphtha	≥1-<2.5%
EINECS: 265-185-4	Flam. Liq. 3, H226	
Index number: 649-330-00-2	STOT RE 1, H372; Asp. Tox. 1, H304	
Reg.nr.: 01-2119458049-33-0002	Aquatic Chronic 2, H411	
	STOT SE 3, H336	

Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: Mere prve pomoæi

### 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Mere za gašenje požara

### 5.1 Extinguishing media

- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

### 5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Continue on page 4

**Trade name: BODY 640 CAVITY WAX****5.6 Fire and explosion Hazards**

- Special protective equipment and fire fighting procedures: Mouth respiratory protective device.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Mere u sluèaju udesa****6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Rukovanje i skladištenje****7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:**

- Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Kontrola izloženosti****8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace:

**108-88-3 toluene**

IOELV (EU) Short-term value: 384 mg/m<sup>3</sup>, 100 ppm

Long-term value: 192 mg/m<sup>3</sup>, 50 ppm

Skin

- Regulatory information IOELV (EU): (EU) 2019/1831

- Additional information: The lists valid during the making were used as basis.

## **Trade name: BODY 640 CAVITY WAX**

### **8.2 Exposure controls**

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Store protective clothing separately.
  - Avoid contact with the skin.
  - Avoid contact with the eyes and skin.
- Respiratory protection:
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- Eye/face protection



Tightly sealed goggles

- Body protection: Protective work clothing

## **SECTION 9: Fizička i hemijska svojstva**

### **9.1 Information on basic physical and chemical properties**

#### · General Information

- |  |  |
|--|--|
| · Physical state   | Fluid  |
| · Colour:  | Brown  |
| · Odour:   | Characteristic   |
| · Odour threshold:   | Not determined.  |
| · Melting point/freezing point:                            | Undetermined.  |
| · Boiling point or initial boiling point and boiling range | 36 °C (64742-49-0 Naphtha (petroleum), hydrotreated light) |
| · Flammability   | Flammable.   |
| · Lower and upper explosion limit                          |  |
| · Lower:   | Not determined.  |
| · Upper:   | Not determined.  |

Continue on page 6  
RS

## **Trade name: BODY 640 CAVITY WAX**

· Flash point:	23 - 60 °C
· Autoignition temperature:	296 °C
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	370 hPa
· Density and/or relative density	
· Density at 20 °C:	0.822 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
<b><u>9.2 Other information</u></b>	
· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Solvent content:	
· Organic solvents:	26.1 %
· VOC (EC)	470.9 g/l
· Solids content (volume):	9.3 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

## Trade name: **BODY 640 CAVITY WAX**

- Desensitised explosives Void

### SECTION 10: Reaktivnost i stabilnost

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
  - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toksikološki podaci

#### · **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

Oral LD50 24,857 mg/kg

##### 108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

##### 68037-49-0 Sulfonic acids, C10-18-alkane, sodium salts

Oral LD50 500 mg/kg (ATE)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Causes damage to the central nervous system through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### · **11.2 Information on other hazards**

- Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ekotoksikološki podaci

#### · **12.1 Toxicity**

- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

#### · **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**Trade name: BODY 640 CAVITY WAX**

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- Remark: Harmful to fish
- Additional ecological information:
- General notes:  
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Harmful to aquatic organisms

**SECTION 13: Odlaganje**

- **13.1 Waste treatment methods**
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**

---

- HP3 Flammable
- HP4 Irritant - skin irritation and eye damage
- HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
- HP10 Toxic for reproduction
- HP14 Ecotoxic
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

**SECTION 14: Podaci o transportu**


- **14.1 UN number or ID number**
- ADR, IMDG, IATA UN1263
- **14.2 UN proper shipping name**
- ADR UN1263 PAINT
- IMDG, IATA PAINT
- **14.3 Transport hazard class(es)**
- ADR



- Class 3 (F1) Flammable liquids.



**Trade name: BODY 640 CAVITY WAX**

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· <b>14.4 Packing group</b>	
· ADR, IMDG, IATA	III
· <b>14.5 Environmental hazards:</b>	
· Marine pollutant:	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

**SECTION 15: Regulatorni podaci**

·3Y

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

## · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## · Hazard pictograms



GHS02 GHS07 GHS08

## · Signal word Danger

## Trade name: **BODY 640 CAVITY WAX**

- Hazard-determining components of labelling:  
 Low boiling point hydrogen treated naphtha  
 toluene  
 Naphtha (petroleum), hydrotreated light
- Hazard statements  
 H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H361d Suspected of damaging the unborn child.  
 H336 May cause drowsiness or dizziness.  
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II  
 None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))  
 None of the ingredients is listed.
- Annex II - REPORTABLE EXPLOSIVES PRECURSORS  
 None of the ingredients is listed.
- Regulation (EC) No 273/2004 on drug precursors  
 108-88-3 toluene: 3
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors  
 108-88-3 toluene: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

### SECTION 16: Ostali podaci

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.

## Trade name: **BODY 640 CAVITY WAX**

- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

### Classification according to Regulation (EC) No 1272/2008

Flammable liquids

Bridging principles

Skin corrosion/irritation

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Reproductive toxicity

Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated exposure)

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

### Contact:

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

Date of previous version: 02.11.2021

Version number of previous version: 12

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

\* Data compared to the previous version altered.

**Trade name: BODY 640 CAVITY WAX****Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC9b** Fillers, putties, plasters, modelling clay**Process category PROC7** Industrial spraying**Article category AC2** Machinery, mechanical appliances, electrical/electronic articles**Environmental release category ERC5** Use at industrial site leading to inclusion into/onto article**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** Use only on hard ground.**Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

**Other operational conditions affecting consumer exposure** No special measures required.**Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Pregnant women should strictly avoid inhalation or skin contact.

**Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**Trade name: BODY 640 CAVITY WAX**· **Environmental protection measures**· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· **Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging· **Exposure estimation**· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.