

1 Identification**1.1 Product identifier**Trade name: **700 PAINT REMOVER**

Article number: 338

Restrictions

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

Application of the substance / the mixture

Paint remover

Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

H.B. BODY S.A
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
email: hbbody@hbbody.com

Information department:

HB BODY S.A.
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com**1.4 Emergency telephone number:** CHEMTRECK : 800-494-9300**2 Hazard(s) identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 2

H371 May cause damage to the central nervous system and the visual organs.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

US

Trade name: 700 PAINT REMOVER

(Contd. of page 1)



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labeled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labeling:
dichloromethane
toluene
methanol
4-methylpentan-2-one
- Hazard statements
H225 Highly flammable liquid and vapor.
H302 Harmful if swallowed.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to the central nervous system and the visual organs.
H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
- P330 Rinse mouth.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 700 PAINT REMOVER

(Contd. of page 2)

- Classification system:
- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 75-09-2	dichloromethane	80-<90%
EINECS: 200-838-9	☠ Carcinogenicity 2, H351	
Index number: 602-004-00-3	⚠ Acute Toxicity - Oral 4, H302	
RTECS: PA 8050000		
CAS: 67-56-1	methanol	5-<10%
EINECS: 200-659-6	⚠ Flammable Liquids 2, H225	
Index number: 603-001-00-X	⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331	
RTECS: PC 1400000	☠ Specific Target Organ Toxicity - Single Exposure 1, H370	
CAS: 108-10-1	4-methylpentan-2-one	1-<5%
EINECS: 203-550-1	⚠ Flammable Liquids 2, H225	
Index number: 606-004-00-4	☠ Carcinogenicity 2, H351	
RTECS: SA 9275000	⚠ Acute Toxicity - Inhalation 4, H332; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	
CAS: 108-88-3	toluene	1-<5%
EINECS: 203-625-9	⚠ Flammable Liquids 2, H225	
Index number: 601-021-00-3	☠ Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304	
RTECS: XS 5250000	⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336	
CAS: 8002-74-2	Paraffin waxes and Hydrocarbon waxes	1-<5%
EINECS: 232-315-6		
RTECS: RV 0350000		

4 First-aid measures

- **4.1 Description of first aid measures**
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.

(Contd. on page 4)
US

Trade name: 700 PAINT REMOVER

(Contd. of page 3)

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Immediately call a doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* **5 Fire-fighting measures**

- **5.1 Extinguishing media**
- Suitable extinguishing agents:
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- Protective equipment: Mouth respiratory protective device.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

* **6 Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals
- PAC-1:

 - 75-09-2 dichloromethane: 200 ppm
 - 67-56-1 methanol: 530 ppm
 - 108-10-1 4-methylpentan-2-one: 75 ppm
 - 108-88-3 toluene: 67 ppm
- PAC-2:

 - 75-09-2 dichloromethane: 560 ppm
 - 67-56-1 methanol: 2,100 ppm
 - 108-10-1 4-methylpentan-2-one: 500 ppm
 - 108-88-3 toluene: 560 ppm
- PAC-3:

 - 75-09-2 dichloromethane: 6,900 ppm
 - 67-56-1 methanol: 7200* ppm
 - 108-10-1 4-methylpentan-2-one: 3000* ppm

(Contd. on page 5)
US

Trade name: 700 PAINT REMOVER

(Contd. of page 4)

108-88-3 toluene: 3700* ppm

7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility: Not required.
Further information about storage conditions:
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

75-09-2 dichloromethane

PEL Short-term value: 125 ppm
Long-term value: 25 ppm
see 29 CFR 1910.1052

REL See Pocket Guide App. A

TLV Long-term value: 50 ppm
BEI, A3

67-56-1 methanol

PEL Long-term value: 260 mg/m³, 200 ppm
REL Short-term value: 325 mg/m³, 250 ppm
Long-term value: 260 mg/m³, 200 ppm
Skin

TLV Short-term value: 250 ppm
Long-term value: 200 ppm
Skin; BEI

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm
REL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 75 ppm
Long-term value: 20 ppm
BEI, A3

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

(Contd. on page 6)
US

Trade name: 700 PAINT REMOVER

(Contd. of page 5)

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, OTO, A4

8002-74-2 Paraffin waxes and Hydrocarbon waxes

REL Long-term value: 2 mg/m³

TLV Long-term value: 2 mg/m³

· **Regulatory information**

PEL: Guide to Occupational Exposure Values (OSHA PELs)

REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

· **Ingredients with biological limit values:**

75-09-2 dichloromethane

BEI 0.3 mg/L

Medium: urine

Time: end of shift

Parameter: Dichloromethane (semi-quantitative)

67-56-1 methanol

BEI 15 mg/L

Medium: urine

Time: end of shift

Parameter: Methanol (background, nonspecific)

108-10-1 4-methylpentan-2-one

BEI 1 mg/L

Medium: urine

Time: end of shift

Parameter: MIBK

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L

Medium: urine

Time: end of shift

Parameter: Toluene

0.3 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

· Additional information: The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 7)

US

Trade name: 700 PAINT REMOVER

(Contd. of page 6)

- Breathing equipment:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

- | | |
|----------------------------------|--|
| Form: | Fluid |
| Color: | According to product specification |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 40 °C (104 °F) |
| · Flash point: | < 23 °C (< 73.4 °F) |
| · Flammability (solid, gaseous): | Highly flammable. |
| · Auto igniting: | 455 °C (851 °F) |
| · Decomposition temperature: | Not determined. |
| · Ignition temperature: | Product is not selfigniting. |
| · Danger of explosion: | Risk of explosion by shock, friction, fire or other sources of ignition. |
| · Explosion limits: | |
| Lower: | 13 Vol % |

(Contd. on page 8)
US

Trade name: 700 PAINT REMOVER

(Contd. of page 7)

Upper:	22 Vol %
· Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
· Density at 20 °C (68 °F):	1.16 g/cm ³ (9.6802 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	97.4 %
VOC content:	14.58 %
	169.1 g/l / 1.41 lb/gal
Solids content:	2.0 %
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity:
Harmful if swallowed.
- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 1,931 mg/kg (rat)
Inhalative LC50/4 h 29.7-31.3 mg/l

75-09-2 dichloromethane

Oral LD50 1,600 mg/kg (rat)
Inhalative LC50/4 h 88 mg/l (rat)

67-56-1 methanol

Oral LD50 5,628 mg/kg (rat)
Dermal LD50 15,800 mg/kg (rabbit)
Inhalative LC50/4 h 3 mg/l (ATE)

108-10-1 4-methylpentan-2-one

Oral LD50 2,080 mg/kg (rat)

(Contd. on page 9)
US

Trade name: 700 PAINT REMOVER

(Contd. of page 8)

Dermal LD50 16,000 mg/kg (rab)
Inhalative LC50/4 h 11 mg/l (ATE)
8.3-16.6 mg/l (rat)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)
Dermal LD50 12,124 mg/kg (rabbit)
Inhalative LC50/4 h 5,320 mg/l (mouse)

- Primary irritant effect:
 - on the skin: Based on available data, the classification criteria are not met.
 - on the eye: Based on available data, the classification criteria are not met.
- Sensitization: Based on available data, the classification criteria are not met.
- Additional toxicological information:
 - Carcinogenic categories
 - IARC (International Agency for Research on Cancer)

 - 75-09-2 dichloromethane: 2A
 - 108-10-1 4-methylpentan-2-one: 2B
 - 108-88-3 toluene: 3
 - NTP (National Toxicology Program)

 - 75-09-2 dichloromethane: R
 - OSHA-Ca (Occupational Safety & Health Administration)

 - 75-09-2 dichloromethane
 - Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - Carcinogenicity
Suspected of causing cancer.
 - Reproductive toxicity
Suspected of damaging fertility or the unborn child.
 - Specific target organ toxicity - single exposure
May cause damage to the central nervous system and the visual organs.
 - Specific target organ toxicity - repeated exposure
May cause damage to organs through prolonged or repeated exposure.
 - Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
 - General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
 - PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
 - vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

US
(Contd. on page 10)

Trade name: 700 PAINT REMOVER

(Contd. of page 9)

13 Disposal considerations

13.1 Waste treatment methods

- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
· Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

14.1 UN-Number

- DOT, ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

- DOT Paint related material
- ADR UN1263 PAINT RELATED MATERIAL, special provision 640D
- IMDG, IATA PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

- DOT



- Class 3 Flammable liquids
- Label 3
- ADR



- Class 3 (F1) Flammable liquids
- Label 3
- IMDG, IATA



- Class 3 Flammable liquids
- Label 3

14.4 Packing group

- DOT, ADR, IMDG, IATA II

14.5 Environmental hazards:

- Marine pollutant: No

14.6 Special precautions for user

- Warning: Flammable liquids
- Hazard identification number (Kemler code): 33
- EMS Number: F-E,S-E
- Stowage Category B

(Contd. on page 11)

Trade name: 700 PAINT REMOVER

(Contd. of page 10)

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- Transport/Additional information:
 - ADR
 - Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
 - IMDG
 - Limited quantities (LQ) 5L
 - Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, II

* **15 Regulatory information**

·3YE

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

- Sara
- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):

75-09-2 dichloromethane

67-56-1 methanol

108-10-1 4-methylpentan-2-one

108-88-3 toluene

- TSCA (Toxic Substances Control Act):

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

75-09-2 dichloromethane: ACTIVE

67-56-1 methanol: ACTIVE

108-10-1 4-methylpentan-2-one: ACTIVE

108-88-3 toluene: ACTIVE

8002-74-2 Paraffin waxes and Hydrocarbon waxes: ACTIVE

- Hazardous Air Pollutants

75-09-2 dichloromethane

67-56-1 methanol

108-10-1 4-methylpentan-2-one

108-88-3 toluene

- Proposition 65

- Chemicals known to cause cancer:

75-09-2 dichloromethane

108-10-1 4-methylpentan-2-one

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 12)

US

Trade name: 700 PAINT REMOVER

(Contd. of page 11)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol
108-10-1 4-methylpentan-2-one
108-88-3 toluene

· Cancerogenity categories

· EPA (Environmental Protection Agency)

75-09-2 dichloromethane: L
108-10-1 4-methylpentan-2-one: I
108-88-3 toluene: II

· TLV (Threshold Limit Value)

75-09-2 dichloromethane: A3
108-88-3 toluene: A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

75-09-2 dichloromethane

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

dichloromethane
toluene
methanol
4-methylpentan-2-one

· Hazard statements

H225 Highly flammable liquid and vapor.
H302 Harmful if swallowed.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to the central nervous system and the visual organs.
H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

(Contd. on page 13)

Trade name: 700 PAINT REMOVER

(Contd. of page 12)

- P330 Rinse mouth.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapor.
 - H301 Toxic if swallowed.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H311 Toxic in contact with skin.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H332 Harmful if inhaled.
 - H336 May cause drowsiness or dizziness.
 - H351 Suspected of causing cancer.
 - H361 Suspected of damaging fertility or the unborn child.
 - H370 Causes damage to organs.
 - H373 May cause damage to organs through prolonged or repeated exposure.
- Department issuing SDS: Department of Quality Control
- Contact:
 - H.B BODY S.A
 - Ms Olympia Stamkou
 - Ph: +30 2310 790 032
 - fax: +30 2310 790 033
- Date of preparation / last revision 03/17/2023
- * Data compared to the previous version altered.