

1 Identification**1.1 Product identifier**Trade name: **741 ACRYL SLOW THINNER**

Article number: 173

Application of the substance / the mixture

Thinner, Diluent

Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

H.B. BODY S.A

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

email: hbody@hbody.com

Information department:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbody.com

email: hbody@hbody.com

1.4 Emergency telephone number: CHEMTRECK : 800-494-9300**2 Hazard(s) identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 Flame

Flammable Liquids 3

H226

Flammable liquid and vapor.



GHS08 Health hazard

Aspiration Hazard 1

H304

May be fatal if swallowed and enters airways.



GHS05 Corrosion

Eye Damage 1

H318

Causes serious eye damage.



GHS07

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 1)

Skin Irritation 2 H315 Causes skin irritation.
Specific Target Organ Toxicity - Single Exposure 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labeled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS05 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling:
butan-1-ol
Solvent naphtha (petroleum), light arom.
n-butyl acetate
1-methoxy-2-propanol
- Hazard statements
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a poison center/doctor if you feel unwell.
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 2)

- Classification system:
- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 123-86-4	n-butyl acetate	30-<35%
EINECS: 204-658-1	Flammable Liquids 3, H226	
Index number: 607-025-00-1	Specific Target Organ Toxicity - Single Exposure 3, H336	
RTECS: AF 7350000		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	30-<35%
EINECS: 265-199-0	Flammable Liquids 3, H226	
Index number: 649-356-00-4	Aspiration Hazard 1, H304	
	Acute Toxicity - Inhalation 4, H332; Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 71-36-3	butan-1-ol	10-<15%
EINECS: 200-751-6	Flammable Liquids 3, H226	
Index number: 603-004-00-6	Eye Damage 1, H318	
RTECS: EO 1400000	Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	
CAS: 107-98-2	1-methoxy-2-propanol	10-<15%
EINECS: 203-539-1	Flammable Liquids 3, H226	
Index number: 603-064-00-3	Acute Toxicity - Inhalation 3, H331	
RTECS: UB 7700000	Specific Target Organ Toxicity - Single Exposure 3, H336	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	10-<15%
EINECS: 203-603-9	Flammable Liquids 3, H226	
Index number: 607-195-00-7		
CAS: 112-07-2	2-butoxyethyl acetate	10-<15%
EINECS: 203-933-3	Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332	
Index number: 607-038-00-2	Flammable Liquids 4, H227	
RTECS: KJ 8925000		

4 First-aid measures

- **4.1 Description of first aid measures**
- General information: Immediately remove any clothing soiled by the product.

(Contd. on page 4)
US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 3)

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* **5 Fire-fighting measures**

· **5.1 Extinguishing media**

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

· Protective equipment: No special measures required.

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

* **6 Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

123-86-4 n-butyl acetate: 5 ppm

71-36-3 butan-1-ol: 60 ppm

107-98-2 1-methoxy-2-propanol: 100 ppm

108-65-6 2-methoxy-1-methylethyl acetate: 50 ppm

112-07-2 2-butoxyethyl acetate: 15 ppm

· PAC-2:

123-86-4 n-butyl acetate: 200 ppm

71-36-3 butan-1-ol: 800 ppm

107-98-2 1-methoxy-2-propanol: 160 ppm

108-65-6 2-methoxy-1-methylethyl acetate: 1,000 ppm

112-07-2 2-butoxyethyl acetate: 35 ppm

(Contd. on page 5)
US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 4)

- PAC-3:
 - 123-86-4 n-butyl acetate: 3000* ppm
 - 71-36-3 butan-1-ol: 8000** ppm
 - 107-98-2 1-methoxy-2-propanol: 660 ppm
 - 108-65-6 2-methoxy-1-methylethyl acetate: 5000* ppm
 - 112-07-2 2-butoxyethyl acetate: 210 ppm

7 Handling and storage

7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Information about protection against explosions and fires:
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: Unsuitable material for receptacle: glass or ceramic.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep receptacle tightly sealed.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

- Components with limit values that require monitoring at the workplace:
 - The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 - At this time, the remaining constituent has no known exposure limits.

123-86-4 n-butyl acetate

- PEL Long-term value: 710 mg/m³, 150 ppm
- REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm
- TLV Short-term value: 150 ppm
Long-term value: 50 ppm

71-36-3 butan-1-ol

- PEL Long-term value: 300 mg/m³, 100 ppm
- REL Ceiling limit value: 150 mg/m³, 50 ppm
Skin
- TLV Long-term value: 20 ppm

107-98-2 1-methoxy-2-propanol

- REL Short-term value: 540 mg/m³, 150 ppm
Long-term value: 360 mg/m³, 100 ppm
- TLV Short-term value: 100 ppm
Long-term value: 50 ppm
A4

108-65-6 2-methoxy-1-methylethyl acetate

- WEEL Long-term value: 50 ppm

(Contd. on page 6)
US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 5)

112-07-2 2-butoxyethyl acetate

REL Long-term value: 33 mg/m³, 5 ppm

TLV Long-term value: 20 ppm
A3

· Regulatory information

PEL: Guide to Occupational Exposure Values (OSHA PELs)

REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

· Additional information: The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

* **9 Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

Form: Fluid

(Contd. on page 7)
US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 6)

· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-soluble (in water).
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	116-118 °C (240.8-244.4 °F)
· Flash point:	23 - 60 °C (73.4 - 140 °F)
· Flammability (solid, gaseous):	Flammable.
· Auto igniting:	270 °C (518 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	20 Vol %
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)
· Density at 20 °C (68 °F):	0.89288 g/cm ³ (7.45108 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	10-12 mPas
Kinematic at 40 °C (104 °F):	7-9 mm ² /s
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	892.9 g/l / 7.45 lb/gal
Solids content:	0.0 %
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

US
(Contd. on page 8)

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 7)

11 Toxicological information

11.1 Information on toxicological effects

- Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 7,900 mg/kg (rat)
Dermal LD50 15,800 mg/kg
Inhalative LC50/4 h >18.1 mg/l

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)
Dermal LD50 >3,400 mg/kg (rab)
Inhalative LC50/4 h >10.2 mg/l (rat)

71-36-3 butan-1-ol

Oral LD50 790 mg/kg (rat)
Dermal LD50 3,400 mg/kg (rabbit)
Inhalative LC50/4 h 8,000 mg/l (rat)

107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)
Dermal LD50 13,000 mg/kg (rabbit)
Inhalative LC50/4 h 6 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)
Inhalative LC50/4 h 35.7 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral LD50 2,400 mg/kg (rat)
Dermal LD50 1,580 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

- Primary irritant effect:

- on the skin:
Causes skin irritation.

- on the eye:
Causes serious eye damage.

- Sensitization: Based on available data, the classification criteria are not met.

- Additional toxicological information:

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.

- Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 9)
US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 8)

- Reproductive toxicity Based on available data, the classification criteria are not met.
- Specific target organ toxicity - single exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
- Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard
May be fatal if swallowed and enters airways.

* **12 Ecological information**

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

* **13 Disposal considerations**

- **13.1 Waste treatment methods**
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.
Recommended cleansing agent: Water, if necessary with cleansing agents.

* **14 Transport information**

- **14.1 UN-Number**
- DOT, ADR, IMDG, IATA UN1263
- **14.2 UN proper shipping name**
- DOT Paint related material
- ADR UN1263 PAINT RELATED MATERIAL,
ENVIRONMENTALLY HAZARDOUS
- IMDG PAINT RELATED MATERIAL, MARINE POLLUTANT
- IATA PAINT RELATED MATERIAL

(Contd. on page 10)

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 9)

14.3 Transport hazard class(es)

· DOT



· Class

3 Flammable liquids

· Label

3

· ADR



· Class

3 (F1) Flammable liquids

· Label

3

· IMDG



· Class

3 Flammable liquids

· Label

3

· IATA



· Class

3 Flammable liquids

· Label

3

14.4 Packing group

· DOT, ADR, IMDG, IATA

III

14.5 Environmental hazards:

· Marine pollutant:

Product contains environmentally hazardous substances:
Solvent naphtha (petroleum), light arom.

Yes

· Special marking (ADR):

Symbol (fish and tree)

14.6 Special precautions for user

Symbol (fish and tree)

· Hazard identification number (Kemler code):

Warning: Flammable liquids

· EMS Number:

30

· Stowage Category

F-E,S-E

14.7 Transport in bulk according to Annex II of

A

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Remarks:

Special marking with the symbol (fish and tree).

(Contd. on page 11)

US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 10)

- ADR
 - Excepted quantities (EQ)
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- IMDG
 - Limited quantities (LQ)
· Excepted quantities (EQ)
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation":
UN 1263 PAINT RELATED MATERIAL, 3, III,
ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

·3Y

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- None of the ingredients is listed.
- Sara
- Section 355 (extremely hazardous substances):
None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings):
71-36-3 butan-1-ol
112-07-2 2-butoxyethyl acetate
- TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
- Hazardous Air Pollutants
None of the ingredients is listed.
- Proposition 65
- Chemicals known to cause cancer:
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
- Chemicals known to cause developmental toxicity:
None of the ingredients is listed.
- Cancerogenity categories
- EPA (Environmental Protection Agency)
71-36-3 butan-1-ol: D
- TLV (Threshold Limit Value)
112-07-2 2-butoxyethyl acetate: A3
- NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labeled according to the CLP regulation.

(Contd. on page 12)
US

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 11)

· Hazard pictograms



GHS02 GHS05 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

butan-1-ol
Solvent naphtha (petroleum), light arom.
n-butyl acetate
1-methoxy-2-propanol

· Hazard statements

H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a poison center/doctor if you feel unwell.
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapor.
H227 Combustible liquid.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.

(Contd. on page 13)

Trade name: 741 ACRYL SLOW THINNER

(Contd. of page 12)

H315 Causes skin irritation.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Department of Quality Control

· Contact:

H.B BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

· Date of preparation / last revision 03/16/2023

· * Data compared to the previous version altered.

US