



TECHNICAL DATA SHEET No 711

BODY 640 CAVITY WAX

GENERAL TECHNICAL DESCRIPTION

Anti-corrosive formula, containing wax and synthetic resins.

It penetrates into hard-to-access points, forming a brown protective membrane.

It retains its elasticity even at extreme temperatures.

Always apply after the paint procedure.

SURFACE

All closed parts (doors, bonnet and running boards)

External underbody parts of the vehicle

PRETREATMENT/CLEANING OF SUBSTRATE



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER.

Make sure the surface is first wiped dry and then air dried.

PRODUCT APPLICATION



Shake well before using:
2 - 3 min



TS gun
Pressure: 3 - 4 bar (44 - 58 psi)
Apply via gun nozzle or extension tube provided, for hard-to-reach areas.

SPECIFIC GRAVITY

0.82 g/cm³

SOLID CONTENT

(NO THINNER)

38 - 42% Weight

VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 840 g/L.

2004/42/IIIB(e)(840)840

THEORETICAL COVERAGE

5 - 6 m² / l at 100 micron (4 mil) dry film thickness

CLEANING OF EQUIPMENT

Clean after final use with
767 NITRO THINNER

REMARKS

- Allow for additional time for combi spray booths to reach the desired temperature
- Best results when used with HB BODY products



Protect from humidity and freeze



Always close tin after use

STORAGE SHELF LIFE

Guaranteed shelf life of 24 months in unused original containers stored in a cool place (+5°C - +25°C) (41°F - 77°F).



Always wear protective equipment



Follow the application instructions mentioned in this TDS

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

NOVEMBER 2023