

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

### · Other means of identification

· Trade name: **BASECOAT PAINT**

· Article number: B53

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Application of the substance / the mixture Surface protection

### · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· Emergency telephone number:

If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zeland 0800 764 766.

## 2 Hazard(s) Identification

### · Classification of the substance or mixture



GHS02 flame

**Trade name: BASECOAT PAINT**

Flammable liquids – Category 3

H226 Flammable liquid and vapour.

Substances and mixtures which, in contact with water, emit flammable gases, H261 In contact with water releases flammable gases.  
flammable gases – Category 2

GHS07

Skin corrosion/irritation – Category 2

H315 Causes skin irritation.

Specific target organ toxicity (single exposure) – Category 3 H336 May cause drowsiness or dizziness.

**Label elements**

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:  
n-butyl ester (50-<60 %)  
Solvent naphtha (petroleum), light arom. (5-<10 %)
- Hazard statements  
H226 Flammable liquid and vapour.  
H261 In contact with water releases flammable gases.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P223 Keep away from any possible contact with water, because of violent reaction and possible flash fire.  
P231+P232 Handle and store contents under inert gas. Protect from moisture.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards**

- Results of PBT and vPvB assessment  
This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- PBT: Not applicable.
- vPvB: Not applicable.

**3 Composition and Information on Ingredients****Chemical characterisation: Mixtures**

- Description: Mixture of hazardous substances listed below with nonhazardous additions.





**Dangerous components:**

CAS: 123-86-4	n-butyl ester	50-<60%
EINECS: 204-658-1	Flammable liquids – Category 3, H226	
Index number: 607-025-00-1	Specific target organ toxicity (single exposure) – Category 3, H336	
RTECS: AF 7350000		
CAS: 1330-20-7	xylene	10-<15%
Index number: 601-022-00-9	Flammable liquids – Category 3, H226	
	Acute toxicity - dermal – Category 4, H312; Acute toxicity - inhalation – Category 4, H332; Skin corrosion/irritation – Category 2, H315	

Continue on page 3

AU

**Trade name: BASECOAT PAINT**

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	5-<10%
EINECS: 265-199-0	 Flammable liquids – Category 3, H226	
Index number: 649-356-00-4	 Aspiration hazard – Category 1, H304	
	 Acute toxicity - inhalation – Category 4, H332; Specific target organ toxicity (single exposure) – Category 3, H335	
	Specific target organ toxicity (single exposure) – Category 3, H336	
CAS: 7429-90-5	aluminium	1-<5%
EINECS: 231-072-3	 Pyrophoric liquids – Category 1, H250; Pyrophoric solids – Category 1, H250; Substances and mixtures which, in contact with water, emit flammable gases – Category 2, H261	
Index number: 013-001-00-6		
RTECS: BD 0330000		
Additional information: For the wording of the listed hazard phrases refer to section 16.		

**4 First Aid Measures**

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire Fighting Measures**

- **Suitable extinguishing agents:**  
Extinguishing powder. Do not use water.  
CO2. Do not use water.  
Sand. Do not use water.  
Special powder for metal fires. Do not use water.  
General aqueous film forming foam, Carbon dioxide (CO2), dry chemical extinguishing powder or water spray. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Hazardous combustion products**  
Fire will produce a dense black smoke containing hazardous decomposition by products. Exposure to those may be a hazard to health.
- **Advice for firefighters**  
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- **Speial protective equipment and fire fighting procedures:** No special measures required.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

**6 Accidental Release Measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

**Trade name: BASECOAT PAINT****Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

**7 Handling and Storage****Handling:**

- Precautions for safe handling
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.
- Information about fire - and explosion protection:
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.

**Storage:**

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
  - Keep container tightly sealed.
  - Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s)** No further relevant information available.

**8 Exposure controls and personal protection**

- Appropriate engineering controls** No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:**

**123-86-4 n-butyl ester**

WES Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

**1330-20-7 xylene**

WES Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 350 mg/m<sup>3</sup>, 80 ppm

- Regulatory information WES: Workplace exposure standards for airborne contaminants
- DNELs

**ATE (Acute Toxicity Estimates)**

Inhalative DNELs >53.6 mg/m<sup>3</sup>

**1330-20-7 xylene**

Inhalative DNELs 11 mg/m<sup>3</sup> (ATE)

- Additional information: The lists valid during the making were used as basis.

**Personal protective equipment:**

- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the skin.
  - Avoid contact with the eyes and skin.
- Respiratory protection:
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:



Protective gloves

**Trade name: BASECOAT PAINT**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

- Rubber gloves

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

## 9 Physical and Chemical Properties

### General Information

- Appearance:

- Form:

Fluid

- Colour:

According to product specification

- Odour:

Characteristic

- Odour threshold:

Not determined.

- pH-value:**

Mixture is non-soluble (in water).

### Change in condition

- Melting point/freezing point:

Undetermined.

- Initial boiling point and boiling range:

124-128 °C

- Flash point:**

23 - 60 °C

### Flammability

Flammable.

Contact with water liberates extremely flammable gases.

- Autoignition temperature:**

370 °C

- Decomposition temperature:

Not determined.

- Ignition temperature:**

Product is not selfigniting.

- Explosive properties:**

Risk of explosion by shock, friction, fire or other sources of ignition.

- Explosion limits:**

- Lower:

1.2 Vol %

- Upper:

7.5 Vol %

- Vapour pressure at 20 °C:**

10.7 hPa

- Vapour pressure at 50 °C:**

55 hPa

- Density at 20 °C:**

0.9-1.13 g/cm<sup>3</sup>

- Relative density

Not determined.

- Vapour density

Not determined.

- Evaporation rate

Not determined.

- Solubility in / Miscibility with**

- water:

Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water:** Not determined.

Continue on page 6

AU

**Trade name: BASECOAT PAINT**

<b>· Viscosity:</b>	
· Dynamic:	Not determined.
· Kinematic at 20 °C:	0 mm <sup>2</sup> /s
<b>· Solvent content:</b>	
· Organic solvents:	73.7 %
· VOC (EC)	663.2-832.6 g/l
· Solids content (volume):	22.0 %
<b>· Other information</b>	
· Particle characteristics	Not applicable.
· Physical state	Liquid

**10 Stability and Reactivity**

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological Information**

- **Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Dermal LD50 15,456 mg/kg

**123-86-4 n-butyl ester**

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 &gt;5,000 mg/kg (rabbit)

Inhalative LC50/4 h &gt;21 mg/l (rat)

**1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral LD50 &gt;6,800 mg/kg (rat)

Dermal LD50 &gt;3,400 mg/kg (rab)

Inhalative LC50/4 h &gt;10.2 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**Trade name: BASECOAT PAINT**

\* **12 Ecological Information**

· **Toxicity**

· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **Other adverse effects** No further relevant information available.

\* **13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

\* **14 Transport information**

· **UN-Number**

· ADG, IMDG, IATA

UN3148

· **UN proper shipping name**

· ADG

UN3148 WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER)

· IMDG, IATA

WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER)

· **Transport hazard class(es)**

· ADG



· **Class**

4.3 (W1) Substances which, in contact with water, emit flammable gases.

· **Label**

4.3

Continue on page 8  
AU

**Trade name: BASECOAT PAINT**

· IMDG, IATA



· Class	4.3 Substances which, in contact with water, emit flammable gases.
· Label	4.3
· <b>Packing group</b>	
· ADG, IMDG, IATA	II
· <b>Environmental hazards:</b>	
· Marine pollutant:	No
· <b>Special precautions for user</b>	Warning: Substances which, in contact with water, emit flammable gases.
· Hazard identification number (Kemler code):	323
· EMS Number:	F-G,S-N
· Segregation groups	(SGG15) Powdered metals
· Stowage Category	D
· Stowage Code	SW2 Clear of living quarters. SW31 Stow away from potential sources of ignition, as determined in 7.4.2.3.2 or 7.5.2.8 or 7.6.2.2.2, as applicable.
· Handling Code	H1 Keep as dry as reasonably practicable
· Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· ADG	
· Limited quantities (LQ)	500 ml
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	0
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	500 ml
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 3148 WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER), 4.3, II

**15 Regulatory information**

4W

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

**Australian Inventory of Industrial Chemicals**

All ingredients are listed.

Continue on page 9  
AU

**Trade name: BASECOAT PAINT**

- Standard for the Uniform Scheduling of Medicines and Poisons  
1330-20-7 xylene: S6
- Australia: Priority Existing Chemicals  
None of the ingredients is listed.
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:  
n-butyl ester (50-<60 %)  
Solvent naphtha (petroleum), light arom. (5-<10 %)
- Hazard statements  
H226 Flammable liquid and vapour.  
H261 In contact with water releases flammable gases.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P223 Keep away from any possible contact with water, because of violent reaction and possible flash fire.  
P231+P232 Handle and store contents under inert gas. Protect from moisture.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

**16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases  
H226 Flammable liquid and vapour.  
H250 Catches fire spontaneously if exposed to air.  
H261 In contact with water releases flammable gases.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.
- **Department issuing SDS:** Department of Quality Control
- **Contact:**  
HB BODY S.A  
Regulatory Officer  
Ms Athina Kapourani  
Ph: +30 2310 790000

**Trade name: BASECOAT PAINT**

email: a.kapourani@hbbody.com

· \* Data compared to the previous version altered.

AU  
Continue on page 11

**Trade name: BASECOAT PAINT****Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC9a** Coatings and paints, thinners, paint removers**Process category**

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

**Article category AC1** Vehicles**Environmental release category ERC2** Formulation into mixture**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.**Duration and frequency**

5 workdays/week.

Frequency of use:

**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** Use only on hard ground.**Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Keep container dry.

Avoid contact with eyes.

**Other operational conditions affecting consumer exposure** No special measures required.**Other operational conditions affecting consumer exposure during the use of the product**  
Not applicable.**Risk management measures****Worker protection****Organisational protective measures**

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Store in cool, dry place in tightly closed receptacles.

Ensure that suitable extractors are available on processing machines

Do not dilute with water.

**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Continue on page 12

AU

**Trade name: BASECOAT PAINT**

Pregnant women should strictly avoid inhalation or skin contact.

Avoid contact with the eyes.

Tightly sealed goggles

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.